## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

- 1. (Currently Amended) A kneading machine comprising:
  - a rotating tank that is substantially cylindrical; and
- a pair of kneading implements (turning within the tank, with concordant directions of rotation, about two axes parallel to the axis of the tank, which are substantially tangential both to one another and to the circumferential wall of the tank, wherein:
  - each implement comprises at least one arm;
- each arm extends on the periphery, and from one end to the other of the theoretical cylinder that has an axis that is coincident with the respective axis of rotation of said arm, in such a way that said arm describes an orbital movement about the respective axis of rotation;
- each arm, at least for a part of its length, that are synchronized with respect to one another, in inclined with respect to a straight line generatrix of said theoretical cylinder parallel to said axis of rotation of the arm;

4

- the opposite ends of the two arms are staggered with respect to one another,

viewed in the direction of the axis of rotation, by an angle smaller than 180° about said

axis of rotation;

- means are provided for causing said arms to have orbital movements about the

respective axes of rotation such a way that the arms pass simultaneously in the area of

tangency of the respective theoretical cylinders, intersecting one another with opposite

directions of movement on account of the concordant rotation of the two implements-;

wherein the aforesaid angle of staggering of the two opposite ends of each arm is

between 20° and 100°, and is preferably between 20° and 45°.

2. (Original) The kneading machine according to Claim 1, wherein said arms

are inclined in a concordant way with respect to the generatrices of their theoretical cylinders in

such a way that at their intersection in the aforesaid area of tangency they are arranged so that

they cross one another, according to a scissors-like configuration.

3. (Original) The kneading machine according to Claim 2, wherein each arm is

set according to a portion of helix extending on the periphery of its theoretical cylinder, and from

one end to the other of said cylinder, according to an angle smaller than 1800, viewed in the

direction of the axis of rotation.

5

Amendment Under 37 C.F.R. § 1.111 USSN 10/720,139

Attorney Docket Q78175

September 1, 2005

4. (Original) The kneading machine according to Claim 3, wherein the two

aforesaid theoretical cylinders have diameters that are substantially equal and heights that are

substantially equal, the two portions of helix defining on said arms are substantially equal, and

the speeds of rotation of the arms are also substantially equal, so that the area of tangency of the

two arms shifts progressively during their intersection in a direction parallel to the axes of the

two theoretical cylinders and from one end to the other of said cylinders.

5. (Original) The kneading machine according to Claim 1, wherein each of the

aforesaid theoretical cylinders has a diameter that is sufficiently large so that said cylinder has

overall dimensions that exceed the limits of the respective quadrant of tank.

6. (Original) The kneading machine according to Claim 5, wherein the two

kneading implements constitute the only members present inside the tank.

7. (Canceled)

8. (Currently Amended) The kneading machine according to Claim 3, A kneading

machine comprising:

- a rotating tank that is substantially cylindrical; and

6

- a pair of kneading implements turning within the tank, with concordant

directions of rotation, about two axes parallel to the axis of the tank, which are

substantially tangential both to one another and to the circumferential wall of the tank,

wherein:

- each implement comprises at least one arm;
- each arm extends on the periphery, and from one end to the other of the

  theoretical cylinder that has an axis that is coincident with the respective axis of rotation

  of said arm, in such a way that said arm describes an orbital movement about the

  respective axis of rotation;
- each arm, at least for a part of its length, that are synchronized with respect to one another, in inclined with respect to a straight line generatrix of said theoretical cylinder parallel to said axis of rotation of the arm;
- the opposite ends of the two arms are staggered with respect to one another, viewed in the direction of the axis of rotation, by an angle smaller than 180° about said axis of rotation;
- means are provided for causing said arms to have orbital movements about the respective axes of rotation such a way that the arms pass simultaneously in the area of tangency of the respective theoretical cylinders, intersecting one another with opposite directions of movement on account of the concordant rotation of the two implements; wherein the aforesaid angle of staggering of the two opposite 30 ends of each arm is

between 20° and 100°, and is preferably between 20° and 45°,

wherein said arms are inclined in a concordant way with respect to the generatrices of their theoretical cylinders in such a way that at their intersection in the aforesaid area of tangency they are arranged so that they cross one another, according to a scissors-like configuration,

wherein each arm is set according to a portion of helix extending on the periphery of its theoretical cylinder, and from one end to the other of said cylinder, according to an angle smaller than 1800, viewed in the direction of the axis of rotation, and

wherein the aforesaid portion of helix has an angle of inclination between 15° and 40°.

- 9. (Original) The kneading machine according to Claim 8, wherein the aforesaid angle of inclination of the portion of helix is equal to approximately 20°.
- 10. (Original) The kneading machine according to Claim 1, wherein the two arms present respective cutting edges 30, which are set opposite to one another when the two arms 13a cross one another.
- 11. (Original) The kneading machine according to Claim 10, wherein the arms have a cross section of square shape.
- 12. (Original) The machine according to Claim 10, wherein the arms have a cross section of trapezial shape.

- 13. (Original) The kneading machine according to Claim 10, wherein said arms have a cross section of rhomboidal shape.
  - 14. (Canceled)